



CARACTERÍSTICAS / FEATURES

- › Camilla para incubadora con estructura en aluminio de alta resistencia
- › Bandeja completamente plana en acero inoxidable para anclar la incubadora y sus accesorios
- › Empuñaduras con material reforzado que asegura que no se rompan.
- › Burlete de goma para evitar ralladuras y mantener la camilla como nueva durante más tiempo
- › 4 ruedas de ataque para mejorar la carga y reducir el desgaste
- › Patas de extrusión de aluminio que garantizan gran resistencia con un peso muy bajo.
- › Manetas telescópicas para una mejor maniobrabilidad
- › Parada intermedia para efectuar la transferencia

- › Stretcher incubator with structure in high strength aluminium
- › Completely flat inox tray to anchor the incubator and accessories
- › Handle grips with reinforced material that ensures they do not break
- › Rubber weatherstrip to avoid scratches and keep the stretcher looking new for longer
- › 4 attack wheels to improve load and reduce wear
- › Extruded aluminum legs that guarantee great resistance with a very low weight.
- › Telescopic levers for better maneuverability
- › Intermediate stop to carry out the transfer or facilitate the incorporation of the patient



ESPECIFICACIONES TÉCNICAS / TECHNICAL DATA

ANCHO	WIDTH	605 ±5 mm
LARGO	LENGTH	1930 ±5 mm
ALTO	HEIGHT	860 ±5 mm
PUNTOS DE ANCLAJE	ANCHOR POINTS	1525 ±5 mm
ALTURA DE CARGA	LOADING HEIGHT	560 ±5 mm
PESO	WEIGHT	54 Kg

