



CARACTERÍSTICAS / FEATURES

- › Camilla para incubadora con estructura en aluminio de alta resistencia.
- › Bandeja completamente plana en acero inoxidable para anclar la incubadora y sus accesorios.
- › Empuñaduras con material reforzado que asegura que no se rompan.
- › Bultete de goma para evitar ralladuras y mantener la camilla como nueva durante más tiempo.
- › 4 ruedas de ataque para mejorar la carga y reducir el desgaste.
- › Patas de extrusión de aluminio que garantizan gran resistencia con un peso muy bajo.
- › Manetas telescópicas para una mejor maniobrabilidad.
- › Parada intermedia para efectuar o facilitar la transferencia del paciente.

- › Stretcher incubator with structure in high strength aluminium.
- › Completely flat inox tray to anchor the incubator and accessories.
- › Handle grips with reinforced material that ensures they do not break.
- › Rubber weatherstrip to avoid scratches and keep the stretcher looking new for longer.
- › 4 attack wheels to improve load and reduce wear.
- › Extruded aluminum legs that guarantee great resistance with a very low weight.
- › Telescopic levers for better maneuverability.
- › Intermediate stop to carry out the transfer or facilitate the incorporation of the patient.



ESPECIFICACIONES TÉCNICAS / TECHNICAL DATA

ANCHO	WIDTH	560 mm
LARGO	LENGTH	1930 mm
ALTO	HEIGHT	960 mm
PUNTOS DE ANCLAJE	ANCHOR POINTS	1525 mm
ALTURA DE CARGA	LOADING HEIGHT	660 mm
PESO	WEIGHT	52 Kg

