



CINTURONES CON PULSADOR FRONTAL  
BELTS WITH FRONT PUSH-BUTTON

BANDEJA PLANA PINTADA EN NEGRO  
BLACK PAINTED FLAT TRAY

MANETAS TELESCÓPICAS  
TELESCOPIC HANDLES

4 RUEDAS DE ATAQUE  
4 ATTACK WHEELS

BURLETE ANTI-GOLPES  
ANTI-SHOCK RUBBER WEATHERSTRIP

PATINES PARA FACILITAR LA CARGA  
SKATES FOR A COMFORTABLE LOADING

2 RUEDAS GIRATORIAS CON FRENO  
2 SWIVEL WHEELS WITH BRAKE

BARANDILLA DE SEGURIDAD  
SAFETY RAIL

MANETAS ERGONÓMICAS  
ERGONOMIC HANDLES

ARCOS DE REFUERZO  
REINFORCEMENT ARCHS

2 RUEDAS GIRATORIAS BLOQUEABLES CON FRENO  
2 LOCKABLE SWIVEL WHEELS WITH BRAKE



## CARACTERÍSTICAS / FEATURES

- › Bandeja completamente plana
- › Con una altura de 300mm cuando la camilla esta plegada
- › Barandilla de seguridad
- › Empuñaduras con material reforzado que asegura que no se rompan.
- › Burlete de goma para evitar ralladuras y mantener la camilla como nueva durante más tiempo
- › 4 ruedas de ataque para mejorar la carga y reducir el desgaste
- › Patas de estampación de aluminio fabricadas con técnicas utilizadas en la industria del automóvil que garantizan gran resistencia con un peso muy bajo.
- › Manetas telescópicas para una mejor maniobrabilidad
- › Parada intermedia para efectuar la transferencia

- › Completely flat tray
- › With a height of 300mm when the stretcher is folded
- › Safety rail
- › Handle grips with reinforced material that ensures they do not break
- › Rubber weatherstrip to avoid scratches and keep the stretcher looking new for longer
- › 4 attack wheels to improve load and reduce wear
- › Aluminum stamping feet manufactured with techniques used in the automotive industry that guarantee great resistance with a very low weight.
- › Telescopic levers for better maneuverability
- › Intermediate stop to carry out the transfer or facilitate the incorporation of the patient

## ESPECIFICACIONES TÉCNICAS / TECHNICAL DATA

ANCHO	WIDTH	570 ±5 mm
LARGO	LENGTH	1930 ±5 mm
ALTO	HEIGHT	940 ±5 mm
ALTURA PLEGADA	HEIGHT WHEN FOLDED	300 ±5 mm
PUNTOS DE ANCLAJE	ANCHOR POINTS	1525 ±5 mm
ALTURA DE CARGA	LOADING HEIGHT	560 ±5 mm
PESO	WEIGHT	45 Kg

