



CARACTERÍSTICAS / FEATURES

- › Camilla para incubadora con estructura en aluminio de alta resistencia.
- › Bandeja completamente plana en acero inoxidable para anclar la incubadora y sus accesorios.
- › Empuñaduras con material reforzado que asegura que no se rompan.
- › Bultete de goma para evitar ralladuras y mantener la camilla como nueva durante más tiempo.
- › 4 ruedas de ataque para mejorar la carga y reducir el desgaste.
- › Patas de extrusión de aluminio que garantizan gran resistencia con un peso muy bajo.
- › Manetas telescópicas para una mejor maniobrabilidad.
- › Parada intermedia para efectuar o facilitar la transferencia del paciente.

- › Stretcher incubator with structure in high strength aluminium.
- › Completely flat inox tray to anchor the incubator and accessories.
- › Handle grips with reinforced material that ensures they do not break.
- › Rubber weatherstrip to avoid scratches and keep the stretcher looking new for longer.
- › 4 attack wheels to improve load and reduce wear.
- › Extruded aluminum legs that guarantee great resistance with a very low weight.
- › Telescopic levers for better maneuverability.
- › Intermediate stop to carry out the transfer or facilitate the incorporation of the patient.



ESPECIFICACIONES TÉCNICAS / TECHNICAL DATA

ANCHO	WIDTH	605 ±5 mm
LARGO	LENGTH	1930 ±5 mm
ALTO	HEIGHT	960 ±5 mm
PUNTOS DE ANCLAJE	ANCHOR POINTS	1525 ±5 mm
ALTURA DE CARGA	LOADING HEIGHT	660 ±5 mm
PESO	WEIGHT	52 Kg

