



CINTURONES CON PULSADOR FRONTAL
BELTS WITH FRONT PUSH-BUTTON

BANDEJA EXTRAIBLE
REMOVABLE TRAY

MANETAS TELESCÓPICAS
TELESCOPIC HANDLES

4 RUEDAS DE ATAQUE
4 ATTACK WHEELS

BURLETE ANTI-GOLPES
ANTI-SHOCK RUBBER WEATHERSTRIP

PATINES PARA FACILITAR LA CARGA
SKATES FOR A COMFORTABLE LOADING

2 RUEDAS GIRATORIAS
2 SWIVEL WHEELS

RUEDAS DE GUIADO VERTICAL
WHEELS FOR VERTICAL MOVEMENT

BARANDILLA DE SEGURIDAD
SAFETY RAIL

MANETAS ERGONÓMICAS
ERGONOMIC HANDLES

ARCOS DE REFUERZO
REINFORCEMENT ARCHES

2 RUEDAS GIRATORIAS BLOQUEABLES CON FRENO
2 LOCKABLE SWIVEL WHEELS WITH BRAKE



CARACTERÍSTICAS / FEATURES

- › Bandeja extraíble y completamente plana
- › Con una altura de 300mm cuando la camilla esta plegada
- › Con posicionadores para bloquear la bandeja una vez colocada en la camilla
- › Barandilla de seguridad incorporada en la litera
- › Empuñaduras con material reforzado que asegura que no se rompan.
- › Burlete de goma para evitar ralladuras y mantener la camilla como nueva durante más tiempo
- › 4 ruedas de ataque para mejorar la carga y reducir el desgaste
- › Patas de perfil de aluminio que garantizan gran resistencia con un peso muy bajo.
- › Manetas telescópicas para una mejor maniobrabilidad.
- › Parada intermedia para efectuar la transferencia.

- › Removable tray, completely flat.
- › With a height of 300mm when the stretcher is folded
- › With positioners to lock the tray once it is placed on the stretcher
- › Safety rail incorporated in the tray.
- › Handle grips with reinforced material that ensures they do not break
- › Rubber weatherstrip to avoid scratches and keep the stretcher looking new for longer
- › 4 loading wheels to improve load and reduce wear
- › Legs made by aluminium extruded profile that guarantee great resistance with a very low weight.
- › Telescopic levers for better maneuverability
- › Intermediate stop to carry out the transfer or facilitate the loading of the corpse.

incorporation of the patient ESPECIFICACIONES TÉCNICAS / TECHNICAL DATA

ANCHO	WIDTH	570 mm
LARGO	LENGTH	1935 mm
ALTO	HEIGHT	960 mm
ALTURA PLEGADA	HEIGHT WHEN FOLDED	300 mm
PUNTOS DE ANCLAJE	ANCHOR POINTS	1525 mm
ALTURA DE CARGA	LOADING HEIGHT	560 mm
PESO	WEIGHT	51 Kg.

